JC02 Recd PCT/PTO 2 8 MAR 2002

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE ATTORNEY'S DOCKET NUMBER FORM PTO-1390 (REV 10-95) **MERCK 2408** TRANSMITTAL LETTER TO THE UNITED STATES U.S. APPLICATION NO. (If known, see 37 CFR §1.5) **DESIGNATED/ELECTED OFFICE (DO/EO/US)** CONCERNING A FILING UNDER 35 U.S.C. §371 10/089223 PRIORITY DATE CLAIMED INTERNATIONAL APPLICATION NO. INTERNATIONAL FILING DATE PCT/EP00/09155 28 SEPTEMBER 1999 **19 SEPTEMBER 2000** TITLE OF INVENTION METHOD FOR BROMINATING ORGANIC COMPOUNDS APPLICANT(S) FOR DO/EO/US FABIAN, Kai, et al Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information: This is a FIRST submission of items concerning a filing under 35 U.S.C. §371. This is a SECOND or SUBSEQUENT submission of items concerning a filing under 35 U.S.C. §371. This express request to begin national examination procedures (35 U.S.C. $\S371(f)$) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. $\S371(b)$ and PCT Articles 22 and 39(1). A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date. A copy of the International Application as filed (35 U.S.C. §371(c)(2)) is transmitted herewith (required only if not transmitted by the International Bureau). has been transmitted by the International Bureau. is not required, as the application was filed in the United States Receiving Office (RO/US). A translation of the International Application into English (35 U.S.C. §371(c)(2)). Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. §371(c)(3)) are transmitted herewith (required only if not transmitted by the International Bureau). have been transmitted by the International Bureau. have not been made; however, the time limit for making such amendments has NOT expired. have not been made and will not be made. A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. §371(c)(3)). An oath or declaration of the inventor(s) (35 U.S.C. §371(c)(4)). 10. A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. §371(c)(5)). Items 11. to 16. below concern document(s) or information included: 11. An Information Disclosure Statement under 37 C.F.R. §§1.97 and 1.98. 12. An assignment document for recording. A separate cover sheet in compliance with 37 C.F.R. §§3.28 and 3.31 is included. 13. A FIRST preliminary amendment. A SECOND or SUBSEQUENT preliminary amendment. 14. A substitute specification. 15. D A change of power of attorney and/or address letter. 16. 🗆 Other items or information:

JC15 Recupet/PTO 28 MAR 2002

U.S. APPLICATION NO. (if kg	ATTORNEY'S DOCKET NUMBER				
U.S. APPLICATION NO. (if known, see 37 CFR \$1.5) 223 INTERNATIONAL APPLICATION NO. PCT/EP00/09155				MERCK 2408	
17. The following	fees are submitted:			CALCULATIONS	PTO USE ONLY
BASIC NAT	IONAL FEE (37 CFR §1.4	192 (a) (1) - (5)):			
Search Report	has been prepared by the E	PO or JPO	\$890.00		
International p	preliminary examination fee	paid to USPTO (37 CFR §1.482	2) \$710.00		
No internation but internation	nal preliminary examination nal search fee paid to USPTO	fee paid to USPTO (37 CFR §1 O (37 CFR §1.445(a)(2))	.482) \$740.00		
Neither intern international s	ational preliminary examina search fee (37 CFR §1.445(a	tion fee (37 CFR §1.482) nor)(2)) paid to USPTO	\$1040.00		
International part and all claims	preliminary examination fee satisfied provisions of PCT	paid to USPTO (37 CFR §1.48; Article 33(2)-(4)	2) \$100.00		
	ENTER APPI	ROPRIATE BASIC FI	EE AMOUNT =	\$890.00	
Surcharge of \$130.00 for months from the earliest	or furnishing the oath or decl t claimed priority date (37 C	aration later than .F.R. $\S1.492(e)$).	□ 30		
ÇLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	19 - 20 =	0	x \$ 18.00	\$0.00	
Independent claims	2 - 3 =	0	x \$ 84.00	\$0.00	
MULTIPLE DEPENDE	ENT CLAIM(S) (if applicabl	e)	+ \$ 280.00		
	TO	TAL OF ABOVE CAL	CULATIONS =	\$890.00	
Reduction of 1/2 for fili	ing by small entity, if applica	able. A Verified Small Entity St	tatement must also be		
			SUBTOTAL =	\$890.00	
Processing fee of \$130.0 months from the earlies	00 for furnishing the English t claimed priority date (37 C	translation later than 20	30		
		TOTAL NA	TIONAL FEE =	\$890.00	
Fee for recording the en an appropriate cover sho	nclosed assignment (37 C.F.I. eet (37 C.F.R. §§3.28, 3.31).	R. §1.21(h)). The assignment m. \$40.00 per property.	ust be accompanied by		
		TOTAL FEES	S ENCLOSED =	\$890.00	
				Amount to be refunded:	
				charged:	
a. A check in	the amount of \$890.00	to cover the above fees i	s enclosed.		
b. Please cha A duplicate	arge my Deposit Account e copy of this sheet is enclose	No. 13-3402 in the amount	of \$	to cover the above fee	es.
c. The Comm	issioner is hereby authorized	I to charge any additional fees w	which may be required,	or credit any overpaym	nent to
Deposit Ac	count No. <u>13-3402.</u> A	duplicate copy of this sheet is e	nclosed.		
NOTE: Where revive (37 C.F.	e an appropriate time li R. §1.137(a) or (b)) mu	imit under 37 C.F.R. §§1.4 st be filed and granted to	494 or 1.495 has no restore the applica	ot been met, a petit ation to pending sta	ion to atus.
i `	NDENCE TO: Customer Numb	_) A		
PATEN	T TRADEMARK OFFICE		IN C	Sh. # 32,004	
11900-			SIGNATURE		
			Anthony J	Zelano	
	23599		NAME	- Zeiuno	
Filed: 28 MARC			27,969		
AJZ:kmo				ON NUMBER	

JC13 Rec'd PCT/PTO 28 MAR 2002

IN THE UNITED STATES DESIGNATED/ELECTED OFFICE

International Application No.

PCT/EP00/09155

International Filing Date

19 SEPTEMBER 2000

Priority Date(s) Claimed

28 SEPTEMBER 1999

Applicant(s) (DO/EO/US)

FABIAN, Kai, et al

Title: METHOD FOR BROMINATING ORGANIC COMPOUNDS

PRELIMINARY AMENDMENT

Commissioner for Patents Washington, D.C. 20231

SIR:

Prior to calculating the national fee, and prior to examination in the National Phase of the above-identified International application, please amend as follows:

IN THE CLAIMS:

- 3. (Amended) Process according to Claim 1, characterized in that the microreactor is a static micromixer.
- 4. (Amended) Process according to Claim 1, characterized in that the microreactor is connected to a capillary, preferably a heatable capillary, via an outlet.
- 5. (Amended) Process according to Claim 1, characterized in that the volume of the microreactor is $\leq 10 \,\mu l$, preferably $\leq 1 \mu l$.
- 6. (Amended) Process according to Claim 1, characterized in that the microreactor is heatable.

- 7. (Amended) Process according to Claim 1, characterized in that the microreactor has channels having a diameter of from 10 to $1000\mu m$, preferably from 20 to $800 \mu m$, particularly preferably from 30 μm to $400 \mu m$.
- 8. (Amended) Process according to Claim 1, characterized in that the reaction mixture flows through the microreactor at a flow rate of from 0.1 μ m/min to 10 ml/min, preferably from 1 μ l/min to 1 ml/min.
- 9. (Amended) Process according to Claim 1, characterized in that the residence time of the compounds employed in the microreactor, where appropriate in the microreactor and the capillaries, is ≤ 3 hours, preferably ≤ 1 hour.
- 10. (Amended) Process according to Claim 1, characterized in that it is carried out at a temperature of from -90 to +150°C, preferably from -20 to +40°C, particularly preferably from -10 to +20°C.
- 11. (Amended) Process according to Claim 1, characterized in that the course of the reaction is monitored by chromatography, preferably gas chromatography, and where appropriate regulated.
- 12. (Amended) Process according to Claim 1, characterized in that the brominated product is isolated from the reaction mixture by extraction or precipitation.
- 13. (Amended) Process according to Claim 1, characterized in that the brominating reagent employed is elemental bromine, dibromoisocyanuric acid, N-bromosuccinimde, hypobromous acid, organic hypobromites, preferably trifluoroacetyl hypobromite, N-bromoacetamide, N-bromophthalimide, pyridinium perbromide and/or dioxane dibromide.
- 14. (Amended) Process according to Claim 1, characterized in that the catalyst employed is iodine, mineral acids, preferably sulphuric acid or nitric acid, and/or Lewis acids, preferably aluminum halides, iron halides, zinc halides or antimony halides.

- 2 -

- 15. (Amended) Process according to Claim 1, characterised in that between 0.1 and 100 mol%, preferably between 1 and 10 mol%, of the catalyst are employed, based on the amount of organic compound employed.
- 18. (Amended) Bromination microreactor according to Claim 16, characterized in that the residence zone is a capillary, preferably a heatable capillary.
- 19. (Amended) Bromination microreactor according to Claim 16, characterised in that it is heatable.

<u>REMARKS</u>

The purpose of this Preliminary Amendment is to eliminate multiple dependent claims in order to avoid the additional fee. Applicants reserve the right to reintroduce claims to canceled combined subject matter.

Attached hereto is a marked-up version of the changes made to the claims by the current amendment. The attached pages are captioned "Version With Markings to Show Changes Made".

Respectfully submitted,

Anthony J. Zelano, Reg. No. 27,969

Attorney for Applicants

MILLEN, WHITE, ZELANO & BRANIGAN, P.C.

Arlington Courthouse Plaza 1

2200 Clarendon Boulevard, Suite 1400

Arlington, VA 22201

Direct Dial: 703-812-5311 Facsimile: 703-243-6410

Email: zelano@mwzb.com

AJZ:kmo

Filed: 28 MARCH 2002

VERSION WITH MARKINGS TO SHOW CHANGES MADE

Claims 3 -15, 18 and 19 were amended as follows:

- 3. (Amended) Process according to Claim 1-or 2, characteriszed in that the microreactor is a static micromixer.
- 4. (Amended) Process according to one of Claims 1 to 3, characteriszed in that the microreactor is connected to a capillary, preferably a heatable capillary, via an outlet.
- 5. (Amended) Process according to one of Claims 1 to 4, characteriszed in that the volume of the microreactor is $\leq 10 \,\mu$ l, preferably $\leq 1 \mu$ l.
- 6. (Amended) Process according to one of Claims 1 to 5, characteriszed in that the microreactor is heatable.
- 7. (Amended) Process according to one of Claims 1 to 6, characteriszed in that the microreactor has channels having a diameter of from 10 to $1000\mu m$, preferably from 20 to $800 \mu m$, particularly preferably from 30 μm to $400 \mu m$.
- 8. (Amended) Process according to one of Claims 1 to 7, characteriszed in that the reaction mixture flows through the microreactor at a flow rate of from 0.1 μm/min to 10 ml/min, preferably from 1 μl/min to 1 ml/min.
- 9. (Amended) Process according to one of Claims 1 to 8, characteriszed in that the residence time of the compounds employed in the microreactor, where appropriate in the microreactor and the capillaries, is ≤ 3 hours, preferably ≤ 1 hour.

- 10. (Amended) Process according to one of Claims 1 to 9, characteriszed in that it is carried out at a temperature of from -90 to +150°C, preferably from -20 to +40°C, particularly preferably from -10 to +20°C.
- 11. (Amended) Process according to one of Claims 1 to 10, characteriszed in that the course of the reaction is monitored by chromatography, preferably gas chromatography, and where appropriate regulated.
- 12. (Amended) Process according to one of Claims 1 to 11 1, characteriszed in that the brominated product is isolated from the reaction mixture by extraction or precipitation.
- 13. (Amended) Process according to one of Claims 1 to 12, characteriszed in that the brominating reagent employed is elemental bromine, dibromoisocyanuric acid, N-bromosuccinimde, hypobromous acid, organic hypobromites, preferably trifluoroacetyl hypobromite, N-bromoacetamide, –bromophthalimide, pyridinium perbromide and/or dioxane dibromide.
- 14. (Amended) Process according to one of Claims 1 to 13, characteriszed in that the catalyst employed is iodine, mineral acids, preferably sulphuric acid or nitric acid, and/or Lewis acids, preferably aluminum halides, iron halides, zinc halides or antimony halides.
- 15. (Amended) Process according to one of Claims 1 to 14, characterised in that between 0.1 and 100 mol%, preferably between 1 and 10 mol%, of the catalyst are employed, based on the amount of organic compound employed.
- 18. (Amended) Bromination microreactor according to Claim 16 or 7, characteriszed in that the residence zone is a capillary, preferably a heatable capillary.
- 19. (Amended) Bromination microreactor according to one of Claims 16 to 18, characterised in that it is heatable.

Merck Patent Gesellschaft mit beschränkter Haftung 64271 Darmstadt

Processes for the bromination of organic compounds

Processes for the bromination of organic compounds

The present invention relates to processes for the bromination of organic compounds, and to bromination microreactors for carrying out these processes.

5

20

25

30

The bromination of organic compounds is a process which is carried out very often in the chemical industry and whose great importance is also reflected in numerous publications on this subject.

However, performance of brominations on an industrial scale is associated with safety problems and risks. Firstly, use is frequently made of highly toxic chemical substances which even on their own represent a considerable risk to people and the environment, and secondly brominations often proceed very highly exothermically, and consequently there is an increased risk of explosion when these reactions are carried out on an industrial scale. The procurement of official approval in accordance with the German Federal Emissions Protection Act (BGBI) I No. 71 of 26.10.1998, p. 3178) for the operation of plants for the bromination of organic compounds on an industrial scale is therefore associated with considerable effort.

The object of the present invention was therefore to provide a novel process for the bromination of organic compounds which can be carried out in a simple, reproducible manner with increased safety for people and the environment and with good yields. A further object was to provide an apparatus for carrying out this process.

This object was achieved in accordance with the invention by the provision of novel processes for the bromination of organic compounds in which the organic compound in liquid or dissolved form is mixed with a brominating reagent in liquid or dissolved form, if desired in the presence of a catalyst in liquid or dissolved form in at least one microreactor and reacted for a residence time, and the brominated organic compound is isolated from the reaction mixture.

For the purposes of the invention, a microreactor is taken to mean a reactor having a volume of \leq 100 μ l in which the liquids and/or solutions are mixed intimately at least once. The volume of the microreactor is preferably \leq 10 μ l,

particularly preferably $\leq 1 \,\mu$ l. A microreactor is preferably made from thin silicon structures bonded to one another.

The microreactor is preferably a miniaturised flow reactor, particularly preferably a static micromixer. The microreactor is very particularly preferably a static micromixer as described in WO 96/30113, which is hereby introduced by way of reference and is regarded as part of the disclosure.

5

10

15

20

25

30

35

A microreactor of this type preferably has small channels in which liquids and/or chemical compounds in the form of solutions are preferably mixed with one another due to the kinetic energy of the flowing liquids and/or solutions.

The channels of the microreactor preferably have a diameter of from 10 to 1000 μ m, particularly preferably from 20 to 800 μ m and very particularly preferably from 30 μ m to 400 μ m.

The liquids and/or solutions are preferably pumped into the microreactor in such a way that they flow through the latter at a flow rate of from 0.1 µl/min to 1 ml/min, particularly preferably from 1 µl/min to 1 ml/min.

In accordance with the invention, the microreactor is preferably heatable.

For the purposes of the invention, the residence time is taken to mean the time between mixing of the organic compounds, any catalysts and brominating reagents or solutions thereof and work-up of this reaction solution for analysis or isolation of the desired product(s).

The residence time necessary in the processes according to the invention depends on various parameters, such as, for example, the reactivity of the organic compounds, catalysts and brominating reagents employed, the desired degree of bromination or the temperature. It is possible for the person skilled in the art to match the residence time to these parameters and thus to achieve an optimum course of the reaction. The residence time of the reaction solution in the microreactor, where appropriate in the microreactor and the residence zone, is preferably ≤ 3 hours, in particular ≤ 1 hour.

In accordance with the invention, the microreactor is preferably connected to at least one residence zone, preferably a capillary, particularly preferably a heatable capillary, via an outlet. After they have mixed in the microreactor,

the liquids and/or solutions are passed into this residence zone or capillary in order to extend their residence time.

The reaction mixture is likewise preferably passed through two or more microreactors connected in parallel or in series. This achieves an extension of the residence time, even at an increased flow rate, and the bromination reaction components employed are converted virtually completely into the brominated organic compound(s) desired.

In a further preferred embodiment of the process according to the invention, the number and/or arrangement of the channels in one or more microreactor(s) are varied in such a way that the residence zone is extended, again resulting in virtually complete conversion into the desired brominated organic compound(s) at an increased flow rate.

The residence time of the reaction solution in the system employed comprising at least one microreactor and, if desired, a residence zone can also be set through the choice of the flow rates of the liquids and/or solutions employed.

The processes according to the invention can be carried out in a very broad temperature range, which is essentially restricted by the temperature resistance of the materials employed for the construction of the microreactor, any residence zone and further constituents, such as, for example, connections and seals, and by the physical properties of the solutions and/or liquids employed. The processes according to the invention are preferably carried out at a temperature of from -90 to +150°C, particularly preferably from -20 to +40°C, very particularly preferably from -10 to +20°C.

The processes according to the invention can be carried out either continuously or batchwise. They are preferably carried out continuously.

For carrying out the processes according to the invention for the bromination of organic compounds, it is necessary for the bromination reaction to be carried out in the homogeneous liquid phase, since otherwise the channels present in the microreactors become blocked.

35

30

The course of the bromination reaction in the processes according to the invention can be monitored using various analytical methods known to the person skilled in the art and where appropriate regulated. The course of the reaction is preferably monitored by chromatography, particularly preferably by gas chromatography, and where appropriate regulated.

5

10

15

20

25

30

The brominated organic compounds can likewise be isolated by various methods known to the person skilled in the art. The brominated product(s) is (are) preferably isolated from the reaction mixture by extraction, preferably with an organic solvent, or by precipitation, preferably with an organic solvent and/or water, particularly preferably with water.

Organic compounds which can be employed in the processes according to the invention are all organic compounds which are known to the person skilled in the art as substrates of bromination reactions.

The organic compounds employed are preferably aromatic or heteroaromatic compounds. These aromatic or heteroaromatic compounds include both monocyclic and polycyclic compounds, as well as compounds which have a monocyclic and/or polycyclic, homo- or heteroaromatic basic structure or part-structure, for example in the form of substituents. The term "organic compounds" is also taken to include organometallic compounds whose organic moieties are susceptible to bromination.

The organic compounds employed are likewise preferably aldehydes or ketones which have at least one hydrogen atom in the α -position to the carbonyl group, and unsaturated aliphatic compounds.

The aromatic compounds employed are particularly preferably alkylated aromatic compounds, very particularly preferably toluene, xylene or mesitylene, benzene, naphthalene, azulene, anthracene, phenanthrene, pyrene, fluorene, quinones, such as, for example, ortho- and para-benzoquinone, naphthoquinones, fluorenones, anthrones, phenanthrones, anthraquinones and/or derivatives thereof.

The heteroaromatic compounds employed are particularly preferably oxygencontaining, heteroaromatic compounds and/or derivatives thereof, very particularly preferably furans, such as, for example, benzo-fused furans, dibenzo-furans, dibenzodioxanes, pyrylium cations or benzopyranones. Particular preference is likewise given to nitrogen-containing, heteroaromatic compounds and/or derivatives thereof, such as, for example, pyrroles, pyrazoles, imidazoles, triazoles, tetrazoles, pyridines, pyrazines, pyrimidines, pyridinium salts, triazines, tetrazines, pyridine N-oxides, benzo-fused pyrroles, such as, for example, indoles, carbazoles, benzimidazoles or benzotriazoles, phenazine, quinolines, isoquinolines, cinnolines, quinazolines, quinazolines, phenanthroline, bipyridyls and higher homologues thereof, acridines, acridones, and/or pyrene. Particular preference is furthermore given to sulfur-containing, heteroaromatic compounds and/or derivatives thereof, such as, for example, thiophenes, benzo-fused thiophenes, in particular benzothiophenes or dibenzothiophenes, and acenaphthylenes, thiazoles, isothiazoles, biphenylenes, purines, benzothiadiazoles, oxazoles and/or isoxazoles.

5

10

15

20

25

30

35

Brominating reagents which can be employed in the processes according to the invention are all brominating reagents known to the person skilled in the art. The brominating reagents employed are preferably elemental bromine, dibromoisocyanuric acid, N-bromosuccinimide, hypobromous acid, organic hypobromites, particularly preferably trifluoroacetyl hypobromite, N-bromoacetamide, N-bromophthalimide, pyridinium perbromide and/or dioxane dibromide.

It is essential for the processes according to the invention that the organic compounds, alkylating reagents and any catalysts employed are either themselves liquid or are in dissolved form. If these compounds are not already in liquid form themselves, they must therefore be dissolved in a suitable solvent before the processes according to the invention are carried out. The solvents employed are preferably halogenated hydrocarbons, particularly preferably dichloromethane, chloroform, tetrachloromethane or tetrachloroethane, esters, particularly preferably ethyl acetate, ethers, particularly preferably tetrahydrofuran, diethyl ether or tert-butyl methyl ether, carboxylic acids, particularly preferably acetic acid, or mixtures thereof.

The molar ratio in the processes according to the invention between the organic compound and the brominating reagent employed depends firstly on the reactivity of the organic compounds, catalysts and brominating reagents

employed, and secondly on the desired degree of bromination. The degree of bromination itself depends on a number of parameters in addition to the concentration of the reagents employed, such as, for example, temperature, type of catalyst or residence time. It is possible for the person skilled in the art to match the various parameters to the respective bromination reaction in such a way that the desired mono- or polybrominated compound is obtained.

5

10

15

20

25

30

35

Depending on the reactivity of the organic compounds and brominating reagents employed, it may be advantageous and in some cases even necessary to employ catalysts in the process according to the invention in order to increase the rate of the bromination reaction. The catalysts employed are preferably elemental iodine, mineral acids, particularly preferably sulfuric acid or nitric acid, and/or Lewis acids, particularly preferably aluminium halides, iron halides, zinc halides or antimony halides.

The amount of catalyst employed in the process according to the invention is preferably between 0.1 and 100 mol%, particularly preferably between 1 and 10 mol%, based on the amount of organic compound employed.

The invention furthermore relates to an bromination microreactor for carrying out the process according to the invention. This bromination microreactor has at least one mixing element and, if desired, a residence zone, and its volume, without the volume of the residence zone, is \leq 100 µl, preferably \leq 10 µl, particularly preferably \leq 1 µl.

In a preferred embodiment, the bromination microreactor is a static micromixer.

In a further preferred embodiment of the bromination microreactor, it has a residence zone which is a capillary which is preferably connected to an outlet of the bromination microreactor. The capillary is preferably a heatable capillary.

The bromination microreactor is likewise preferably itself heatable.

In the processes according to the invention, the risk to people and the environment due to released chemicals is considerably reduced. Furthermore, the risk of an explosion in the very highly exothermic bromination reactions is reduced, inter alia due to improved mass and heat transport compared with conventional systems. Official approval in accordance with the German Federal Emissions Protection Act (BGBI. I No. 71 of 26.10.1998, p. 3178) for the operation of plants for carrying out the processes according to the invention is therefore easier to obtain. It is also particularly advantageous that the process according to the invention can be carried out continuously. This enables them to be carried out more quickly and at lower cost than conventional processes, and it is possible to prepare any desired amounts of the brominated organic compounds without major measurement and control effort. The course of the bromination reaction can be regulated very quickly in the processes according to the invention. The bromination of organic compounds by the processes according to the invention also enables better control via the reaction duration and reaction temperature than is possible in the conventional processes. The temperature can be selected individually and kept constant in each volume element of the system. The brominated organic products can thus be obtained in very good and reproducible yields.

The invention is explained below with reference to examples. These examples serve merely to explain the invention and do not restrict the general inventive idea.

25

5

10

15

20

Examples

Example 1

Bromination of mesitylene using elemental bromine:

15

20

25

5

The bromination of mesitylene (1) using elemental bromine was carried out in a static micromixer (Technical University of Ilmenau, Faculty of Machine Construction, Qr.-Ing. Norbert Schwesinger, P.O. Box 100565, D-98684, Ilmenau) having a physical size of 0.8 mm x 0.8 mm x 0.6 mm and a total volume of 0.125 µl and a total pressure loss of about 1000 Pa. The static micromixer was connected to a Teflon capillary having an internal diameter of 0.25 mm and a length of 1 m via an outlet and an Omnifit medium-pressure HPLC connector (Omnifit, Germany). The temperatures of the static micromixer and the Teflon capillary were regulated in an water-filled jacketed vessel thermostatted to 10°C.

30

35

In order to prepare a solution of mesitylene, 1.2 g (0.01 mol) of mesitylene were diluted with tetrachloromethane to a total volume of 2 ml. In order to prepare a solution of elemental bromine, 1.7 g (0.011 mol) of bromine were diluted with tetrachloromethane to a total volume of 2 ml. The two solutions were subsequently transferred into the static micromixer using a metering pump (Harvard Apparatus Inc., Pump 22, South Natick, Massachusetts, USA) and 2 ml polypropylene syringes (B. Braun Melsungen AG, Germany). The flow rate here was set to 10 ml/min. The mixed reaction solution was subsequently passed into 2 ml of an HPLC buffer solution comprising acetonitrile and 1% trifluoroacetic acid in the ratio 1:1 (Merck, Darmstadt) in order to

terminate the bromination reaction. The reaction mixture was evaluated by combined GC/MS analysis. The reaction mixture comprised 88 area-% of the chromatogram of the monobrominated product (2), 9 area-% of the dibrominated product (3) and 3 area-% of the unbrominated mesitylene (1).

5

In order to determine the preparative yield of the brominated reaction products, the mixed reaction solution was stirred into a beaker containing 50 ml of water. The system comprising static micromixer and Teflon capillary was subsequently rinsed firstly with 10 ml of water and subsequently with 10 ml of dichloromethane. The combined liquid phases were then stirred for 20 minutes and subsequently extracted three times with 20 ml of diethyl ether each time. The combined ethereal extracts were dried over magnesium sulfate and freed from solvent under reduced pressure, giving 1.7 g (corresponding to 73% of the theoretical yield) of a brownish oil, whose content of monobrominated product (2) was determined by combined GC/MS analysis as 85 area-% of the chromatogram.

15

10

Example 2

20

The set-up and performance were as in Example 1, but the flow rate was set to 20 μ l/min. Combined GC/MS analysis of the reaction mixture obtained in this way gave a composition of 51 area-% of the chromatogram of the monobrominated product (2), 47 area-% of the dibrominated product (3) and 2 area-% of mesitylene brominated in the methyl side chain.

25

PATENT CLAIMS

- Process for the bromination of organic compounds, characterised in that
 the organic compound in liquid or dissolved form is mixed with a brominating reagent in liquid or dissolved form, if desired in the presence of a
 catalyst in liquid or dissolved form, in at least one microreactor and
 reacted for a residence time, and the brominated organic compound is
 isolated from the reaction mixture.
- 2. Process according to Claim 1, characterised in that the microreactor is a miniaturised flow reactor.

5

20

30

- 3. Process according to Claim 1 or 2, characterised in that the microreactor is a static micromixer.
- 4. Process according to one of Claims 1 to 3, characterised in that the microreactor is connected to a capillary, preferably a heatable capillary, via an outlet.
 - 5. Process according to one of Claims 1 to 4, characterised in that the volume of the microreactor is ≤ 10 μl, preferably ≤ 1 μl.
 - 6. Process according to one of Claims 1 to 5, characterised in that the microreactor is heatable.
- 7. Process according to one of Claims 1 to 6, characterised in that the microreactor has channels having a diameter of from 10 to 1000 μm, preferably from 20 to 800 μm, particularly preferably from 30 μm to 400 μm.
 - 8. Process according to one of Claims 1 to 7, characterised in that the reaction mixture flows through the microreactor at a flow rate of from 0.1 µl/min to 10 ml/min, preferably from 1 µl/min to 1 ml/min.
 - 9. Process according to one of Claims 1 to 8, characterised in that the residence time of the compounds employed in the microreactor, where appropriate in the microreactor and the capillaries, is ≤ 3 hours, preferably ≤ 1 hour.

- .10. Process according to one of Claims 1 to 9, characterised in that it is carried out at a temperature of from -90 to +150°C, preferably from -20 to +40°C, particularly preferably from -10 to +20°C.
- 11. Process according to one of Claims 1 to 10, characterised in that the course of the reaction is monitored by chromatography, preferably gas chromatography, and where appropriate regulated.

10

15

20

25


- 12. Process according to one of Claims 1 to 11, characterised in that the brominated product is isolated from the reaction mixture by extraction or precipitation.
- 13. Process according to one of Claims 1 to 12, characterised in that the brominating reagent employed is elemental bromine, dibromoisocyanuric acid, N-bromosuccinimide, hypobromous acid, organic hypobromites, preferably trifluoroacetyl hypobromite, N-bromoacetamide, N-bromophthalimide, pyridinium perbromide and/or dioxane dibromide.
- 14. Process according to one of Claims 1 to 13, characterised in that the catalyst employed is iodine, mineral acids, preferably sulphuric acid or nitric acid, and/or Lewis acids, preferably aluminium halides, iron halides, zinc halides or antimony halides.
- 15. Process according to one of Claims 1 to 14, characterised in that between 0.1 and 100 mol%, preferably between 1 and 10 mol%, of the catalyst are employed, based on the amount of organic compound employed.
- 16. Bromination microreactor having at least one mixing element and, if desired, a residence zone, characterised in that the volume of the bromination microreactor, without the volume of the residence zone, is \leq 10 μ l, preferably \leq 1 μ l.
- 17. Bromination microreactor according to Claim 16, characterised in that it is a static micromixer.
- 18. Bromination microreactor according to Claim 16 or 7, characterised in that the residence zone is a capillary, preferably a heatable capillary.

19. Bromination microreactor according to one of Claims 16 to 18, characterised in that it is heatable.

- 13 -

A B S T R A 🖓

The present invention relates to processes for the bromination of organic compounds, and to bromination microreactors for carrying out these processes.



	_	$\overline{}$	~
/	Ì	6)
	1	C	

POWER OF ATTORNEY: As a named inventor, I hereby appoint I. William Millen (19,544); John L. White (17,746); Anthony J. Zelano (27,969); Alan E.J. Branigan (20,565); John R. Moses (24,983); Harry B. Shubin (32,004); Brion P. Heaney (32,542); Richard J. Traverso (30,595); John A. Sopp (33,103); Richard M. Lebovitz (37,067); James E. Ruland (37,432); Nancy Axelrod (44,014); Jennifer J. Branigan (40,921); Robert E. McCarthy, (46,044); Jonathan G. Brown (47,451); and Csaba Henter (50,908) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

Send Correspondence to: Customer No. 23599

Telephone No. 703/243-6333 Direct Telephone Calls to:

YES YES

YES

☐] NO

NO




23599

PATENT TRA DEMARK OFFICE

Combined Declaration for Patent Application and Power of Attorney (Continued)
(Includes Reference to PCT International Applications)

ATTORNEY'S DOCKET NUMBER

			FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
: ~		FULL NAME OF INVENTOR	FABIAN	Kai	SECOND SIVEN IVAME
10	۲ ₂				
	0	RESIDENCE &	crry 69259 Wilhelmsfeld	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP German
	1	CITIZENSHIP	Comment of the Commen	DEX	· · ·
		POST OFFICE	STREET Oberer Langerain 13	CITY	STATE & ZIP CODE/COUNTRY
		ADDRESS	-		Germany
	2	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
			STOLDT	Joeran	
20	7 ~	RESIDENCE &	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
-	2	CITIZENSHIP	64331 Weiterstadt	DEX	German
	-	POST OFFICE	STREET	CITY	STATE & ZIP CODE/COUNTRY
		ADDRESS	Kreuzstrasse 11		Germany
	<u> </u>	EUL MANE	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
		FULL NAME OF INVENTOR	WURZIGER,	Hanns	
	2		CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
2/8	0	RESIDENCE & CITIZENSHIP	64291 Darmstadt_	7) F V	German
5-0-	3	· · · · · · · · · · · · · · · · · · ·	STREET	CITY	STATE & ZIP CODE/COUNTRY
		POST OFFICE		CITY	
		ADDRESS	Greinstrasse 7b		Germany
		FULL NAME	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
	$\left \begin{array}{c}2\\0\\4\end{array}\right $	OF INVENTOR	SCHWESINGER	Norbert	
11-180		RESIDENCE &	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
400		CITIZENSHIP	85386 Eching	DEX	German
		POST OFFICE	STREET	CITY	STATE & ZIP CODE/COUNTRY
		ADDRESS	Bahnstrasse 35		Germany
	-		FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
		FULL NAME OF INVENTOR	2	THE TOTAL CONTROL OF THE PARTY	SEGNE GIVEN NAME
	2	OF INVENTOR	CITY	STATE OR FOREIGN COUNTRY	COLINEDA OF CAMAZENEANID
	0	RESIDENCE & CITIZENSHIP	CHY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
	5		STREET	CUTTY	
		POST OFFICE	SIREEI	CITY	STATE & ZIP CODE/COUNTRY
		ADDRESS			
		FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
	2				
	0	RESIDENCE &	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
	6	CITIZENSHIP			
		POST OFFICE	STREET	CITY	STATE & ZIP CODE/COUNTRY
		ADDRESS			
		FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME
ľ	2				
	ō	RESIDENCE &	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
	7	CITIZENSHIP			
	'	POST OFFICE	STREET	CITY	STATE & ZIP CODE/COUNTRY
		ADDRESS			



Combined Declaration for Patent Application and Power of Attorney (Continued) (Includes Reference to PCT International Applications)

ATTORNEY'S DOCKET NUMBER

(1.1.0.1		C1 International Applications)	P. Walter		
2	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME	
0 8	RESIDENCE & CITY CITIZENSHIP		STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP	
0	POST OFFICE ADDRESS	STREET	CITY	STATE & ZIP CODE/COUNTRY	
2	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME	
0	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP	
7	POST OFFICE ADDRESS	STREET	CITY	STATE & ZIP CODE/COUNTRY	
2	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME	
1 0	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP	
	POST OFFICE ADDRESS	STREET	CITY	STATE & ZIP CODE/COUNTRY	
•	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME	
2	RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP	
1	POST OFFICE ADDRESS	STREET	CITY	STATE & ZIP CODE/COUNTRY	
2	FULL NAME OF INVENTOR	FAMILY NAME	FIRST GIVEN NAME	SECOND GIVEN NAME	
1 2	RESIDENCE & CITIZENSHIP	СІТҮ	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP	
_	POST OFFICE ADDRESS	STREET	СІТҮ	STATE & ZIP CODE/COUNTRY	

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

SIGNATURE OF INVENTOR 201	DATE	SIGNATURE OF INVENTOR 207	DATE
V yel	23.08.2002		
SIGNATURE OF INVENTOR 202	DATE 23.08.2002	SIGNATURE OF INVENTOR 208	DATE
SIGNATURE OF INVENTOR 263	DATE 23.08.2002	SIGNATURE OF INVENTOR 209	DATE
SIGNATURE OF INVENTOR 200 COLLO	DATE 23.08.2002	SIGNATURE OF INVENTOR 210	DATE
SIGNATURE OF INVENTOR 205	DATE	SIGNATURE OF INVENTOR 211	DATE
SIGNATURE OF INVENTOR 206	DATE	SIGNATURE OF INVENTOR 212	DATE